



# Material Safety Data Sheet

Document Code: Putty/MW  
Version: 00

Date of Preparation  
14-JAN-2000

## Section 1 - Product and Company Identification

### PRODUCT NAME & NUMBERS

MINWAX WOOD PUTTY®

3610	Natural Pine	3615	Cherry
3611	Golden Oak	3616	White
3612	Colonial Maple	3617	Walnut
3613	Red Mahogany	3618	Ebony
3614	Early American	3619	Pickled Oak

### PRODUCT CLASS

Vegetable Oil Filler

### HMIS CODES

Health	1
Flammability	0
Reactivity	0

### MANUFACTURER'S NAME

MINWAX Company  
10 Mountainview Road  
Upper Saddle River, NJ 07458

### EMERGENCY TELEPHONE NO.

(216) 566-2917

### INFORMATION TELEPHONE NO.

(800) 523-9299

## Section 2 - Composition/Information on Ingredients

% WT.	CAS No.	Ingredient Name
5	14807-96-6	<b>Talc</b>
		ACGIH TLV TWA 2 Mg/M3 as Resp. Dust
		OSHA PEL TWA 2 Mg/M3 as Resp. Dust
80	471-34-1	<b>Calcium Carbonate.</b>
		ACGIH TLV TWA 10 Mg/M3 as Dust
		OSHA PEL TWA 15 Mg/M3 as Total Dust
		OSHA PEL TWA 5 as Respirable Fraction

## Section 3 - Hazards Identification

### ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

### EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and upper respiratory system. In a confined area vapors in high concentration may cause headache, nausea or dizziness.

### SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

### CANCER INFORMATION

FOR COMPLETE DISCUSSION OF TOXICOLOGY DATA REFER TO SECTION 11.

## Section 4 - First Aid Measures

If INHALED:	If affected, remove from exposure. Restore breathing. Keep warm and quiet.
If on SKIN:	Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.
If in EYES:	Flush eyes with large amounts of water for 15 minutes. Get medical attention.
If SWALLOWED:	Get medical attention.

- Continued -

**Section 5 – Fire Fighting Measures**

FLASH POINT	LEL	UEL
Not Applicable	N.A.	N.A.
FLAMMABILITY CLASSIFICATION		
Not Applicable		
EXTINGUISHING MEDIA		
Carbon Dioxide, Dry Chemical, Foam		
UNUSUAL FIRE AND EXPLOSION HAZARDS		
Not Applicable		
SPECIAL FIRE FIGHTING PROCEDURES		
Not Applicable		

**Section 6 – Accidental Release Measures****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate and remove with inert absorbent.

**Section 7 – Handling and Storage****DOL STORAGE CATEGORY**

Not Applicable

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

**Section 8 – Exposure Controls/Personal Protection****PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

These coatings may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m<sup>3</sup> (total dust), 3 mg./m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg./m<sup>3</sup> (total dust), 5 mg./m<sup>3</sup> (respirable fraction).

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION**

Wear safety spectacles with unperforated sideshields.

## Section 9 – Physical and Chemical Properties

PRODUCT WEIGHT	18.3 lb./gal.	EVAPORATION RATE	Slower than Ether
SPECIFIC GRAVITY	2.2	VAPOR DENSITY	Heavier than Air
BOILING POINT	500-680 °F	MELTING POINT	N.A.
VOLATILE VOLUME	0 %	SOLUBILITY IN WATER	N.A.
VOC	0.00 lbs./gal. (less exempt solvents)		

## Section 10 – Stability and Reactivity

STABILITY - Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION - Will not occur

## Section 11 – Toxicological Information

CHRONIC HEALTH HAZARDS

No ingredient in these products is an IARC, NTP or OSHA listed carcinogen.

TOXICOLOGY DATA

CAS No.	Ingredient Name			
14807-96-6	Talc			
	LC50	RAT	4HR	Not Available
	LD50	RAT		Not Available
471-34-1	Calcium Carbonate.			
	LC50	RAT	4HR	Not Available
	LD50	RAT		6450 MG/KG

## Section 12 – Ecological Information

ECOTOXICOLOGICAL INFORMATION

No Data Available.

## Section 13 – Disposal Considerations

WASTE DISPOSAL METHOD

Waste from these products is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

## Section 14 – Transport Information

DOT PROPER SHIPPING DESCRIPTION: Paint and Related Materials, NOIBN

IATA/IMDG SHIPPING DESCRIPTION: Paint and Related Materials, NOIBN

## Section 15 – Regulatory Information

### SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

No ingredients in these products are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

### CALIFORNIA PROPOSITION 65

WARNING: These products contain a chemical known to the State of California to cause cancer.

### TSCA CERTIFICATION

All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

## Section 16 – Other Information

CANADIAN DISTRIBUTOR: *Consumer Brands Canada Inc.*  
*200 Confederation Parkway*  
*Vaughn, ON L4K 4T8*

NOTE: These products have been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the products. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.